



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 32023

HTX 909

Date of the previous version: 2018-07-31

Revision Date: 2019-02-18

Version 5.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	HTX 909
Number	FMC
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71***
-----------------	--

For further information, please contact:

Contact Point	HSE***
E-mail Address	rm.msds-lubs@total.com***

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670
 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
 In France - Poison centers:
 ANGERS : 02 41 48 21 21
 BORDEAUX : 05 56 96 40 80
 LILLE : 08 00 59 59 59
 LYON : 04 72 11 69 11
 MARSEILLE : 04 91 75 25 25
 NANCY : 03 83 22 50 50
 PARIS : 01 40 05 48 48
 STRASBOURG : 03 88 37 37 37
 TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

REGULATION (EC) No 1272/2008 ****For the full text of the H-Statements mentioned in this Section, see Section 2.2.******Classification**

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008***

Skin sensitization - Category 1*** - (H317)***

Chronic aquatic toxicity - Category 3*** - (H412)***

2.2. Label elements**Labelled according to** REGULATION (EC) No 1272/2008***

Contains Calcium long chain alkaryl sulfonate

Hazard pictograms

**Signal word**

WARNING***

Hazard Statements ***

H317 - May cause an allergic skin reaction

H412 - Harmful to aquatic life with long lasting effects***

Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water***

2.3. Other hazards**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.*****Environmental properties** The product may form an oil film on the water surface that may stop the oxygen exchange.*****Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixture***



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Chemical nature The product is made from synthetic base oils.***
Hazardous ingredients ***

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Phenol, isopropylated, phosphate (3:1)***	273-066-3***	01-2119535109-41	68937-41-7	1-<2.5	STOT RE 2 (H373) Repr. 2 (H361fd) Aquatic Chronic 1 (H410) Chronic M factor 1
Calcium long chain alkaryl sulfonate***	-	-	722503-68-6	1-<2.5	Aquatic Chronic 4 (H413) Skin Sens.1B (H317)
Naphthalene***	202-049-5***	-	91-20-3	0.001-<0.01	Acute Tox. 4 (H302) Carc. 2 (H351) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Acute M factor = 1

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.***

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.***
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.***
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.***
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.***
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.***

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified based on available data.***
Skin contact	May cause an allergic skin reaction.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

4.3. Indication of any immediate medical attention and special treatment needed**Notes to physician** Treat symptomatically.*****Section 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**Suitable Extinguishing Media** Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.*****Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.5.2. Special hazards arising from the substance or mixture**Special Hazard** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Mercaptans. Nitrogen oxides (NO_x).***5.3. Advice for fire-fighters**Special protective equipment for fire-fighters** Wear self-contained breathing apparatus and protective suit.*****Other information** Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.**Section 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**General Information** Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***6.2. Environmental precautions**General Information** Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.***6.3. Methods and material for containment and cleaning up**Methods for containment** Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.*****Methods for cleaning up** Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.***



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

6.4. Reference to other sections**Personal Protective Equipment** See Section 8 for more detail.**Waste treatment** See section 13.**Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**Advice on safe handling** For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.*****Prevention of fire and explosion** Take precautionary measures against static discharges.*****Hygiene measures** Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.***7.2. Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions** Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.*****Materials to Avoid** Strong oxidizing agents.***7.3. Specific end uses**Specific use(s)** Please refer to Technical Data Sheet for further information.*****Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**Exposure limits** Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Chemical Name	European Union
Naphthalene*** 91-20-3	TWA 10 ppm TWA 50 mg/m ³ ***

Legend See section 16

SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Derived No Effect Level (DNEL) ***
DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Phenol, isopropylated, phosphate (3:1)*** 68937-41-7	700 mg/m ³ (inhalation) 2000 mg/kg bw/day (dermal)	16 mg/cm ² (dermal)	0.145 mg/m ³ (inhalation) 0.417 mg/kg bw/day (dermal)	
Naphthalene*** 91-20-3			25 mg/m ³ Inhalation 3.57 mg/kg Dermal	25 mg/m ³ Inhalation

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Phenol, isopropylated, phosphate (3:1)*** 68937-41-7	350 mg/m ³ (inhalation) 100 mg/kg bw/day (dermal) 50 mg/kg bw/day (oral)	8 mg/cm ² (dermal)	0.208 mg/kg bw/day (dermal) 0.040 mg/kg bw/day (oral)	

Predicted No Effect Concentration (PNEC) ***

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Phenol, isopropylated, phosphate (3:1)*** 68937-41-7	0.000310 mg/l (fw) 0.000031 mg/l (mw)	0.185 mg/kg sediment dw (fw) 0.0185 mg/kg sediment dw (mw)	1 mg/kg soil dw		100 mg/l	
Naphthalene*** 91-20-3	0.0024 mg/l fw 0.0024 mg/l mw 0.020 mg/l or	0.0672 mg/kg dw fw 0.0672 mg/kg dw mw	0.0533 mg/kg dw		2.9 mg/l	

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Personal Protective Equipment
General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.***

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.***



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.***

Hand Protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.***

Environmental exposure controls**General Information**

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance		limpid***	
Color		red***	
Physical State @20°C		liquid***	
Odor		Characteristic***	
Odor Threshold		No information available	
<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable***	
Melting point/range		Not applicable***	
Boiling point/boiling range		No information available***	
Flash point ***	>*** 200*** °C*** >*** 392*** °F***		ASTM D92*** ASTM D92***
Evaporation rate		No information available***	
Flammability Limits in Air		***	
upper ***	***	No information available***	***
Lower ***	***	No information available***	***
Vapor Pressure		No information available***	
Vapor density		No information available***	
Relative density	*** 0.943*** _*** 0.953***	@ 15 °C***	ISO 12185***
Density	943*** - *** 953*** kg/m ³ ***	@ 15 °C***	ISO 12185***
Water solubility		Insoluble***	
Solubility in other solvents		No information available***	
logPow		No information available***	
Autoignition temperature		No information available***	
Decomposition temperature		No information available	



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Viscosity, kinematic ***	*** 164*** mm ² /s***	@ 40 °C ***	ISO 3104 ***
Explosive properties	Not explosive***		
Oxidizing Properties	Not applicable***		
Possibility of hazardous reactions	None under normal processing***		

9.2. Other information**Freezing Point**

No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity**General Information**

None under normal processing.***

10.2. Chemical stability**Stability**

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions**Hazardous Reactions**

No dangerous reaction known under conditions of normal use.***

10.4. Conditions to avoid**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.***

10.5. Incompatible materials**Materials to Avoid**

Strong oxidizing agents.***

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Mercaptans. Nitrogen oxides (NO_x).***

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects**Acute toxicity Local effects Product Information****Skin contact**

. May cause an allergic skin reaction.***

Eye contact

. Not classified based on available data.***

SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Inhalation . Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***

Ingestion . Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***

ATEmix (inhalation-dust/mist) 309.00*** mg/l***
ATEmix (inhalation-vapor) 1,340.00*** mg/l***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phenol, isopropylated, phosphate (3:1)***	> 5000 mg/kg (Rat)	>10000 mg/kg (rabbit)	> 200 mg/L (Rat) 1 h
Naphthalene***	LD50 490 mg/kg (Rat)	LD50 2201 mg/kg (Rat)	LD50 (8h) > 500 mg/m ³ (Rat)

Sensitization

Sensitization May cause an allergic skin reaction.***

Specific effects

Carcinogenicity Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. Contains substance(s) listed as carcinogen.***

Chemical Name	European Union
Naphthalene*** 91-20-3	Carc. 2 (H351)

Mutagenicity .***
Germ Cell Mutagenicity Not classified based on available data.***

Reproductive toxicity Not classified based on available data. Contains toxic substance(s) listed as toxic to reproduction.***

Chemical Name	European Union
Phenol, isopropylated, phosphate (3:1)*** 68937-41-7	Repr. 2 (H361fd)

Repeated dose toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure) Not classified based on available data.***

Specific target organ systemic toxicity (repeated exposure) Not classified based on available data.***

Aspiration toxicity Not classified based on available data.***

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).***

SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.***

Acute aquatic toxicity - Product Information***

No information available.***

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Phenol, isopropylated, phosphate (3:1)*** 68937-41-7	EC50(72 h) 2.5-1000 mg/l	LC50(48h) 2.44 mg/l (Daphnia magna)	LC50(96h) 1.6 mg/l (Oncorhynchus mykiss) LC50(96h) 10.8 mg/l (Pimephales promelas)	EC50 > 1000 mg/l bacteria
Naphthalene*** 91-20-3		LC50 (48h) = 2.16 mg/L Daphnia magna EC50 (48h) = 1.96 mg/L Daphnia magna Flow through EC50 (48h) 1.09 - 3.4 mg/L Daphnia magna Static	LC50 (96h) = 1.6 mg/L Oncorhynchus mykiss (flow-through) LC50 (96h) 5.74-6.44 mg/L Pimephales promelas (flow-through) LC50 (96h) 0.91-2.82 mg/L Oncorhynchus mykiss (static) LC50 (96h) = 1.99 mg/L Pimephales promelas (static) LC50 (96h) = 31.0265 mg/L Lepomis macrochirus (static)	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h

Chronic aquatic toxicity - Product Information

No information available.***

Chronic aquatic toxicity - Component Information

No information available.***

Effects on terrestrial organisms

No information available.***

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.***

logPow

No information available***

Component Information

Chemical Name	log Pow
---------------	---------



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Naphthalene*** - 91-20-3	3.3
--------------------------	-----

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.***
Air	Loss by evaporation is limited.***
Water	The product is insoluble and floats on water.***

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.***

12.6. Other adverse effects

General Information No information available.***

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.***
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.***
EWC Waste Disposal No.	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 06.***
Other information	Refer to section 8 for safety and protective measures for disposal personnel.***

Section 14: TRANSPORT INFORMATION

ADR/RID Not regulated

IMDG/IMO Not regulated

ICAO/IATA Not regulated

ADN ***

UN/ID No

ID9006***

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.***



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

Hazard class	9***
Hazard Labels	none***
Environmental hazard	Yes***
Description	ID9006, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9 (Phenol, isopropylated, phosphate (3:1))***
Equipment Requirements	PP***

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

REACH

All substances contained in this mixture have been pre-registered, registered or are exempt from registration in accordance with Regulation (CE) No. 1907/2006 (REACH)***

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
 U.S.A. (TSCA)
 Europe (EINECS/ELINCS/NLP)
 Australia (AICS)***

Further information

No information available***

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available***

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day



SDS # : 32023

HTX 909

Revision Date: 2019-02-18

Version 5.01

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

PEL: Permissible exposure limit

REL: Recommended exposure limit

TLV: Threshold Limit Values

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2019-02-18

Revision Note: *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

LUBGES-AI-31784

1. Exposure scenario

Formulation additives, lubricants and greases, Industrial.

Use Descriptor

Sector of use

SU10 - Formulation

SU3 - Industrial Manufacturing (all)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 - Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15 - Use as laboratory reagent

Environmental Release Category

ERC2 - Formulation of preparations

Specific Environmental Release Category

ATIEL-ATC SpERC 2.Ai-I.v1.

Processes, tasks, activities covered

Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Amounts used

Production volume in EU (tons/year) : 1.00E+04

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.1

Frequency and duration of use

Emission Days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other operational conditions of use affecting environmental exposure

Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs): 5.00E-05

Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 1.50E-11

Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Prevent discharge of undissolved substance to or recover from onsite wastewater

User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system

Treat air emission to provide a typical removal efficiency of (%): 70

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%): 79

Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 1 318 918

Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2. Control of exposure - Workers / Consumers

Product characteristics**Physical State**

Liquid, vapor pressure < 0.5 kPa at STP

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Amounts used

Not applicable.

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management

not applicable

Other operational conditions affecting exposure

Covers percentage substance in the product up to 100 % (unless stated differently).

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures applicable to all activities	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures. Use in contained systems elevated temperature - PROC 2	No other specific measures identified.
Mixing operations (closed systems). Batch processes at elevated temperatures - PROC 3	Provide extract ventilation to points where emissions occur.
Mixing operations (open systems). Batch processes at elevated temperatures - PROC 4; 5	Provide extract ventilation to points where emissions occur. Avoid carrying out activities involving exposure for more than 4 hours.
Mixing operations (open systems) - PROC 4; 5	Provide extract ventilation to points where emissions occur.
Process sampling - PROC 4; 8b	Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Bulk transfers; dedicated facility - PROC 8b	Avoid carrying out operation for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Drum/batch transfers; dedicated facility - PROC 8b	Provide extract ventilation to points where emissions occur.
Drum/batch transfers; non-dedicated facility - PROC 8a	Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 1 hour. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Equipment cleaning and maintenance - PROC 8a; 8b	Drain down and flush system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately.
Drum and small package filling - PROC 9	Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Laboratory activities - PROC 15	Avoid carrying out activities involving exposure for more than 4 hours.
Storage - PROC 1; 2	Store substance within a closed system.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
-----------------------	---

Remarks

Not applicable.

3. Exposure estimation and references

Health

The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product

Environment

Used ECETOC TRA model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>). If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

General

For further information see www.atiel.org/reach/introduction

LUBGES-BI-31784

1. Exposure scenario

General use of lubricants and greases in vehicles or machinery. Industrial.

Use Descriptor

Sector of use

SU3 - Industrial Manufacturing (all)

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Environmental Release Category

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC7 - Industrial use of substances in closed systems

Specific Environmental Release Category

ATIEL-ATC SpERC 4.Bi.v1.

Processes, tasks, activities covered

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Amounts used

Production volume in EU (tons/year) : 2.63E+03

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.1

Frequency and duration of use

Emission Days (days/year): 300

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other operational conditions of use affecting environmental exposure

Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs): 5.00E-05

Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 1.50E-11

Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Prevent discharge of undissolved substance to or recover from onsite wastewater

User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%): 79

Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 347 068

Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2. Control of exposure - Workers / Consumers

Product characteristics

Physical State

liquid

Vapor Pressure

<0.5 kPa

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure	
Contributing Scenarios	Operational conditions and risk management measures
General measures applicable to all activities	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems) - PROC 1	No other specific measures identified.
Initial factory fill of equipment Use in contained systems - PROC 2; 9	No other specific measures identified.
Initial factory fill of equipment (open systems) - PROC 8b	Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.
Operation of equipment containing engine oils and similar Use in contained systems - PROC 1	No other specific measures identified.
Equipment cleaning and maintenance - PROC 8b	Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC 8b	Drain down system prior to equipment break-in or maintenance. Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage - PROC 1; 2	Store substance within a closed system.

2.2b. Control of consumer exposure	
Product Category(ies)	Operational conditions and risk management measures

Remarks
Not applicable.

3. Exposure estimation and references

Health

The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product

Environment

Used ECETOC TRA model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to

at least equivalent levels.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>). If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

General

For further information see www.atiel.org/reach/introduction

LUBGES-BP-31784

1. Exposure scenario

General use of lubricants and greases in vehicles or machinery. Professional.

Use Descriptor

Sector of use

SU22 - Professional uses

Process category

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC20 - Heat and pressure transfer fluids in dispersive, professional use but closed systems

Environmental Release Category

ERC9a - Wide dispersive indoor use of substances in closed systems

ERC9b - Wide dispersive outdoor use of substances in closed systems

Specific Environmental Release Category

ATIEL-ATC SpERC 9.Bp.v1.

Processes, tasks, activities covered

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

2. Operational conditions and risk management measures

2.1. Control of environmental exposure

Amounts used

Production volume in EU (tons/year) : 5.39E+03

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.1

Frequency and duration of use

Emission Days (days/year): 365

Environment factors not influenced by risk management

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

Other operational conditions of use affecting environmental exposure

Negligible wastewater emissions as process operates without water contact.

Release fraction to air from process (after typical onsite RMMs): 5.00E-04

Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04

Release fraction to soil from process (after typical onsite RMMs): 1.00E-03

Technical conditions and measures at process level to prevent release

Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Prevent discharge of undissolved substance to or recover from onsite wastewater

Organizational measures to prevent/limit release from the site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Estimated substance removal from wastewater via domestic sewage treatment (%): 79

Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d): 269

Assumed domestic sewage treatment plant flow (m³/d): 2.00E+03

Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2. Control of exposure - Workers / Consumers

Product characteristics

Physical State

liquid

Vapor Pressure

<0.5 kPa

Concentration of substance in product

Covers percentage substance in the product up to 100 % (unless stated differently).

Frequency and duration of use

Covers daily exposures up to 8 hours (unless stated differently)

Other operational conditions affecting exposure

Assumes use at not more than 20°C above ambient temperature, unless stated differently. Assumes a good basic standard of occupational hygiene is implemented.

2.2a. Control of worker exposure

Contributing Scenarios	Operational conditions and risk management measures
General measures applicable to all activities	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Operation of equipment containing engine oils and similar; Use in contained systems - PROC 1	No other specific measures identified.
Material transfers; non-dedicated facility - PROC 8a	Avoid carrying out activities involving exposure for more than 4 hours. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenance; dedicated facility - PROC 8b; 20	Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage - PROC 1; 2	Store substance within a closed system.

2.2b. Control of consumer exposure

Product Category(ies)	Operational conditions and risk management measures
-----------------------	---

Remarks

Not applicable.

3. Exposure estimation and references

Health

The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product

Environment

Used ECETOC TRA model.

4. Guidance for Downstream User to check compliance with the Exposure scenario

Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>). If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

General

For further information see www.atiel.org/reach/introduction